


MODEL YS 800 CLASS 800 CARBON STEEL SCREWED / SOCKET WELD ''Y'' STRAINER

DRAWING A 100



DESCRIPTION	MATERIAL
BODY	ASTM A105 N
САР	ASTM A105 N
GASKET	SPIRAL WOUND SS
SCREEN	304 SS 1/32 PERF

TEMPER	ATURE	WORKING PRESSURE			
С	F	kPa	P.S.I.		
-29 to 38	-20 to 100	13780	2000		
95	200	13366	1940		
150	300	13056	1895		
200	400	12746	1850		
260	500	11954	1735		

ALL STRAINERS ARE INDIVIDUALLY HYDROSTATICALLY TESTED TO ANSI B16.5

		DIMENSIONS						NET	
SIZE		Α		В		С		WEIGHT	
mm	in.	mm	in.	mm	in.	mm	in.	Kg.	Lbs
6	1/4	79	3 1/8	83	3 1/4	10	3/8	.9	2
10	3/8	79	3 1/8	83	3 1/4	10	3/8	.9	2
15	1/2	79	3 1/8	83	3 1/4	10	3/8	.9	2

FEATURES

BODY HAS A MACHINED SEAT TO HOLD SCREEN SECURELY.

CAP HAS A MACHINED SCREEN HOLDER TO ALIGN SCREEN DURING INSTALLATION AND TO RETAIN SEDIMENT WHEN CAP IS REMOVED.

BODY IS MACHINED TO HOLD CAP GASKET IN A BLOW-OUT PROOF DESIGN.