


MODEL NYS 600 600# ANSI CARBON STEEL SCREWED / SOCKET WELD "Y" STRAINER

DRAWING A 112



DESCRIPTION	MATERIAL
BODY	ASTM A216 GR. WCB
CAP	ASTM A216 GR. WCB
GASKET	SPIRAL WOUND SS
SCREEN	304 SS 1/32 PERF

TEMPER	ATURE	WORKING PRESSURE			
C	F	kPa	P.S.I.		
-29 to 38	-20 to 100	10200	1480		
95	200	9300	1350		
150	300	9060	1315		
200	400	8750	1270		
260	500	8275	1200		

ALL STRAINERS ARE INDIVIDUALLY HYDROSTATICALLY TESTED TO ANSI B16.5

	DIMENSIONS							NET	
SIZE			A B		С		WEIGHT		
mm	in.	mm	in.	mm	in.	mm	in.	Kg.	Lbs
40	1 1/2	142	5 9/16	112	4 3/8	20	3/4	3.6	8
50	2	177	6 15/16	143	5 5/8	25	1	6.8	15

FEATURES

BODY HAS A MACHINED SEAT TO HOLD SCREEN SECURELY.

CAP HAS A MACHINED SCREEN HOLDER TO ALIGN SCREEN DURING INSTALLATION AND TO RETAIN SEDIMENT WHEN CAP IS REMOVED.

BODY IS MACHINED TO HOLD CAP GASKET IN A BLOW-OUT PROOF DESIGN.