


## MODEL YS 600 600# ANSI CARBON STEEL SCREWED / SOCKET WELD "Y" STRAINER

## **DRAWING A 110**



DESCRIPTION	MATERIAL
BODY	ASTM A216 GR. WCB
CAP / COVER	ASTM A216 GR. WCB
STUD	ASTM A193 GR. B7
NUT	ASTM A194 GR. 2H
GASKET	SPIRAL WOUND SS
SCREEN	304 SS 1/8 PERF

TEMPER	ATURE	WORKING PRESSURE			
С	F	kPa	P.S.I.		
-29 to 38	-20 to 100	10200	1480		
95	200	9300	1350		
150	300	9060	1315		
200	400	8750	1270		
260	500	8275	1200		

## ALL STRAINERS ARE INDIVIDUALLY HYDROSTATICALLY TESTED TO ANSI B16.5

	DIMENSIONS					NET			
SIZE		A		В	C		WEIGHT		
mm	in.	mm	in.	mm	in.	mm	in.	Kg.	Lbs
75	3	298	11 3/4	279	11	25	1	25.5	56

## **FEATURES**

BODY HAS A MACHINED SEAT TO HOLD SCREEN SECURELY.

CAP/COVER HAS A MACHINED SCREEN HOLDER TO ALIGN SCREEN DURING INSTALLATION AND TO RETAIN SEDIMENT WHEN CAP/COVER IS REMOVED.

BODY IS MACHINED TO HOLD CAP GASKET IN A BLOW-OUT PROOF DESIGN.