


<b>ALTA</b>	<b>MODEL YS 1500 BC</b> <b>1500# ANSI CARBON STEEL</b> <b>SCREWED / SOCKET WELD</b> <b>"Y" STRAINER BOLTED COVER</b>	<b>DRAWING A 60</b>
-------------	---	---------------------



DESCRIPTION	MATERIAL
BODY	ASTM A216 GR. WCB
COVER	ASTM A216 GR. WCB
STUD	ASTM A193 GR. B7
NUT	ASTM A194 GR. 2H
GASKET	SPIRAL WOUND SS
SCREEN	304 SS 1/16 PERF

TEMPERATURE		WORKING PRESSURE	
C	F	kPa	P.S.I.
-29 to 38	-20 to 100	25546	3705
95	200	23701	3375
150	300	22616	3280
200	400	21857	3170
260	500	20651	2995

**ALL STRAINERS ARE INDIVIDUALLY HYDROSTATICALLY TESTED TO ANSI B16.5**

SIZE		DIMENSIONS				SCREEN REMOVAL		NET WEIGHT			
		A		B						C	
mm	in.	mm	in.	mm	in.	mm	in.	Kg.	Lbs.		
50	2	248	9 3/4	220	8 3/4	25	1	241	9 1/2	25.5	56

## FEATURES

**BODY HAS A MACHINED SEAT TO HOLD SCREEN SECURELY.**

**COVER HAS A MACHINED SCREEN HOLDER TO ALIGN SCREEN DURING INSTALLATION AND TO RETAIN SEDIMENT WHEN COVER IS REMOVED.**

**BODY IS MACHINED TO HOLD COVER GASKET IN A BLOW-OUT PROOF DESIGN.**