


<b>ALTA</b>	<b>MODEL YS 2500</b> <b>2500# ANSI CARBON STEEL</b> <b>SCREWED / SOCKET WELD</b> <b>"Y" STRAINER</b>	<b>DRAWING A 80</b>
-------------	---	---------------------



DESCRIPTION	MATERIAL
BODY	ASTM A216 GR. WCB
COVER	ASTM A216 GR. WCB
STUD	ASTM A193 GR. B7
NUT	ASTM A194 GR. 2H
GASKET	SPIRAL WOUND SS
SCREEN	304 SS 1/8 PERF

TEMPERATURE		WORKING PRESSURE	
C	F	kPa	P.S.I.
-29 to 38	-20 to 100	42540	6170

**ALL STRAINERS ARE INDIVIDUALLY HYDROSTATICALLY TESTED TO ANSI B16.5**

SIZE		DIMENSIONS						SCREEN REMOVAL		NET WEIGHT	
		A		B		C					
mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	Kg.	Lbs.
25	1	140	5 1/2	177	7	15	1/2	203	8	10.4	23
50	2	350	13 3/4	254	10	25	1	330	13	45	100

## **FEATURES**

**BODY HAS A MACHINED SEAT TO HOLD SCREEN SECURELY.**

**COVER HAS A MACHINED SCREEN HOLDER TO ALIGN SCREEN DURING INSTALLATION AND TO RETAIN SEDIMENT WHEN COVER IS REMOVED.**

**BODY IS MACHINED TO HOLD COVER GASKET IN A BLOW-OUT PROOF DESIGN.**