


MODEL NYS 600 LCC 600# ANSI CARBON STEEL SCREWED / SOCKET WELD LOW TEMP "Y" STRAINER

DRAWING L 112



DESCRIPTION	MATERIAL
BODY	ASTM A352 GR. LCC
CAP	ASTM A352 GR. LCC
GASKET	SPIRAL WOUND SS
SCREEN	304 SS 1/32 PERF

TEMPER	ATURE	WORKING PRESSURE			
C	C F		P.S.I.		
-45 to 38	-50 to 100	10340	1500		
95	200	10340	1500		
150	300	10010	1455		
200	400	9666	1405		
260	500	9150	1330		

ALL STRAINERS ARE INDIVIDUALLY HYDROSTATICALLY TESTED TO ANSI B16.5

		DIMENSIONS						NET		
SIZE			A		В		С		WEIGHT	
mm	in.	mm	in.	mm	in.	mm	in.	Kg.	Lbs	
40	1 1/2	142	5 9/16	112	4 3/8	20	3/4	3.6	8	
50	2	177	6 15/16	143	5 5/8	25	1	6.8	15	

FEATURES

BODY HAS A MACHINED SEAT TO HOLD SCREEN SECURELY.

CAP HAS A MACHINED SCREEN HOLDER TO ALIGN SCREEN DURING INSTALLATION AND TO RETAIN SEDIMENT WHEN CAP IS REMOVED.

BODY IS MACHINED TO HOLD CAP GASKET IN A BLOW-OUT PROOF DESIGN.