


MODEL YS 2500 LCC 2500# ANSI CARBON STEEL SCREWED / SOCKET WELD LOW TEMP ''Y'' STRAINER

DRAWING L205



DESCRIPTION	MATERIAL
BODY	ASTM A352 GR. LCC
COVER	ASTM A352 GR. LCC
STUD	ASTM A193 GR. L7M
NUT	ASTM A194 GR. L7M
GASKET	SPIRAL WOUND SS
SCREEN 1"	304 SS 1/16 PERF
SCREEN 2"	304 SS 1/8 PERF

TEMPER	ATURE	WORKING PRESSURE				
С	F	kPa	P.S.I.			
-45 to 38	-50 to 100	43090	6250			
95	200	43090	6250			
150	300	41761	6070			
200	400	40351	5865			
260	500	38115	5540			

ALL STRAINERS ARE INDIVIDUALLY HYDROSTATICALLY TESTED TO ANSI B16.5

		DIMENSIONS						SCREEN		NET		
SIZE		Α			В		С		REMOVAL		WEIGHT	
mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	Kg.	Lbs.	
25	1	140	5 1/2	177	7	15	1/2	203	8	10.4	23	
50	2	350	13 3/4	238	9 3/8	25	1	330	13	45	100	

FEATURES

BODY HAS A MACHINED SEAT TO HOLD SCREEN SECURELY.

COVER HAS A MACHINED SCREEN HOLDER TO ALIGN SCREEN DURING INSTALLATION AND TO RETAIN SEDIMENT WHEN COVER IS REMOVED.

BODY IS MACHINED TO HOLD COVER GASKET IN A BLOW-OUT PROOF DESIGN.